NSN 3040-01-481-2251

Shouldered Shaft - Page 1 of 2

Circular grooved and externally threaded

First End Style:

0.0938 inches

First End Groove Width:

First End Groove Diameter:



View Online at https://aerobasegroup.com/nsn/3040-01-481-2251

0.5938 inches
End Similarity:
Not identical
Second End Style:
Plain
Overall Length:
16.4380 inches
End Application:
Scuttle
First End Distance From End To Groove:
0.6880 inches
First End Keyway Width:
Between 0.2500 inches and 0.2550 inches
First End External Keyway Length:
0.8438 inches
First End Keyway Depth:
0.1250 inches
First End Distance From Keyway Center To End:
1.4219 inches
First End Diameter:
0.7500 inches
First End Distance From Hole Center To End:
0.3438 inches
First End External Thread Length:
0.6880 inches
Second End Diameter:
Between 1.1230 inches and 1.1240 inches
Second End Distance From Hole Center To End:
0.6250 inches
Second End Distance Between Hole Centers:
7.2500 inches
Step Quantity:
4
Largest Step Diameter:
Between 1.1230 inches and 1.1240 inches

First end chamfered 45 degrees 0.0938 wide, second end chamfered 45 degrees 0.1250 wide

Special Features:

NSN 3040-01-481-2251

Shouldered Shaft - Page 2 of 2



Material:
Stainless steel
Material Specification:
Sae-ams-qq-s-763 assn standard single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A23200