# NSN 3040-01-481-2251

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-481-2251

## First End Style:

Circular grooved and externally threaded

#### First End Groove Width:

0.0938 inches

## First End Groove Diameter:

0.5938 inches

#### End Similarity:

Not identical

## Second End Style:

Plain

#### **Overall Length:**

16.4380 inches

#### **End Application:**

Scuttle

#### First End Distance From End To Groove:

0.6880 inches

## First End Keyway Width:

Between 0.2500 inches and 0.2550 inches

#### First End External Keyway Length:

0.8438 inches

## First End Keyway Depth:

0.1250 inches

## First End Distance From Keyway Center To End:

1.4219 inches

#### First End Diameter:

0.7500 inches

## First End Distance From Hole Center To End:

0.3438 inches

## First End External Thread Length:

0.6880 inches

#### Second End Diameter:

Between 1.1230 inches and 1.1240 inches

## Second End Distance From Hole Center To End:

0.6250 inches

## Second End Distance Between Hole Centers:

7.2500 inches

#### **Step Quantity:**

4

## Largest Step Diameter:

Between 1.1230 inches and 1.1240 inches

## **Special Features:**

First end chamfered 45 degrees 0.0938 wide, second end chamfered 45 degrees 0.1250 wide

# NSN 3040-01-481-2251

Shouldered Shaft - Page 2 of 2



Material:

Stainless steel

# Material Specification:

Sae-ams-qq-s-763 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200