NSN 3040-01-484-3394

Control Cam - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3040-01-484-3394

inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	End Application:
2.0000 inches Specific Use: Activates limit switch on aircraft elevator doors Camlength: 22.5625 inches Thickness: 2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.0000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A50800 Mil-std (military Standard):	Aircraft carrier cvn 74
Specific Use: Activates limit switch on aircraft elevator doors Camlength: 22.5625 inches Thickness: 2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig: A50800 Mil-std (military Standard):	Cam Width:
Activates limit switch on aircraft elevator doors Camlength: 22.5625 inches Thickness: 2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: Na Unit Of Measure: Demilitarization: No Filg: A50800 Mil-std (military Standard):	2.0000 inches
Camlength: 22.5625 inches Thickness: 2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: Na Unit Of Measure: Demilitarization: No Fig: A50800 Mil-std (military Standard):	Specific Use:
22.5625 inches Thickness: 2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A50800 Mil-std (military Standard):	Activates limit switch on aircraft elevator doors
Thickness: 2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Camlength:
2.8750 inches Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	22.5625 inches
Special Features: Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Thickness:
Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501 0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	2.8750 inches
0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.000 inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A50800 Mil-std (military Standard):	Special Features:
inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x 10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Steel conforming to abs requirements may be substituted; cam constructed from items 1501 and 1502 on drawing welded together; 1501
10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled 4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	0.7500 inches thick, 12.3125 inches long, first end 1.5000 inches wide for 4.250 inches then tapers down, at 4.6875 inches width is 1.0000
4.00000 inches from the second end centered on the width side Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	inches, at 9.0625 inches tapers up to a width of 2.0000 inches at a length of 10.8125; 1502 2.8750 inches wide x 2.0000 inches thick x
Material: Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	10.2500 inches long, first end internally threaded 1.5000 inches-6unc-2b x 3.1250 inches deep, one 1.2500 inches diameter hole drilled
Steel Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	4.00000 inches from the second end centered on the width side
Material Specification: Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Material:
Mil-s-22698 military specification single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Steel
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Material Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Mil-s-22698 military specification single material response
Unit Of Measure: Demilitarization: No Fiig: A50800 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A50800 Mil-std (military Standard):	N/a
No Fiig: A50800 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A50800 Mil-std (military Standard):	
Fiig: A50800 Mil-std (military Standard):	Demilitarization:
A50800 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A50800
Mil-s-22698 spec	Mil-std (military Standard):
Will 0 22000 0p00.	Mil-s-22698 spec.