NSN 3040-01-484-9634

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-484-9634

First End Style:
Plain
End Similarity:
Not identical
Second End Style:
Flat groove and woodruff keyway
Overall Length:
89.2500 inches
End Application:
Hangar division doors used on aircraft carrier cvn 74
First End Diameter:
Between 8.4980 inches and 8.5000 inches
Second End Distance From End To Flat:
0.7500 inches
Second End Keyway Width:
2.0000 inches
Second End External Keyway Length:
7.0000 inches
Second End Distance From Keyway Center To End:
5.0000 inches
Second End Diameter:
Between 8.2490 inches and 8.2500 inches
Second End Grooved Flat Length:
0.5000 inches
Second End Grooved Flat Depth:
1.1250 inches
Step Quantity:
6
Largest Step Diameter:
8.9375 inches
Surface Finish:
63.0 microinches
Product Name:
Shaft
Special Features:
All keyways to have a 0.0625 radius in bottom corners; from second end, steps up at 9.2500 inches to 8.5000 inches diameter, steps up at
18.7500 inches to 8.5620 inches diameter, steps up at 28.5000 inches to 8.9375 inches diameter, steps down at 67.5000 inches to 8.5100
inches diameter; steps down at 80.1562 to 8.5000 inches diameter; two 2.0000 inches wide x 0.7500 inches deep keyways, first one starts
at 9.0938 inches and stops at 21.0938 inches from first end, second one starts at 19.1250 inches and stops at 28.1250 inches from second
end; both ends have 0.1250 inches x 45 degree chamfer
Material:
Steel
Material Specification:

Mil-s-24093 cl-e type i, ii, or iii military specification single material response or aisi 4140 or b7 assn standard single material response

.

NSN 3040-01-484-9634

Shouldered Shaft - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A23200	

Mil-std (military Standard):

Mil-s-24093 spec.

Shelf Life: