

View Online at <https://aerobasegroup.com/nsn/3040-01-486-3886>

**Outside Diameter:**

2.000 inches

**Thickness:**

Between 2.245 inches and 2.246 inches

**Bore Diameter:**

Between 0.6260 inches and 0.6290 inches

**End Application:**

Los angeles class ssn (688)

**Securing Hole Quantity:**

3

**Angle Between Centerlines Of Securing Holes In Deg:**

90.0

**Screw Thread Series Designator And Location:**

1st hole unc

**Securing Hole Type And Location:**

Threaded-countersunk 1st hole

**Countersunk Hole Angle In Deg And Location:**

90.0 1st hole

**Thread Size And Location:**

0.250 inches 1st hole

**Hole Diameter And Location:**

0.2500 inches 3rd hole err-100 err-100

**Countersink Major Diameter And Location:**

0.2812 any acceptable feet

**Surface Finish And Location:**

63 microinches outside periphery

**Product Name:**

Hub

**Special Features:**

All 3 securing holes are 0.750 in. Nom. From one end. Two parallel sides flattened to 1.750 in. Unthreaded securing holes go through center of flats. Part of retractable bow planes emergency follow-up and xmtr drive assembly

**Material:**

Nickel copper alloy

**Material:**

Nickel alloy

**Style Designator:**

Plain round

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A231a0