## NSN 3040-01-486-4251

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-486-4251 First End Style: External threaded **End Similarity:** Not identical Second End Style: Cross drilled hole and splined (straight) **Overall Length:** 5.6300 inches **End Application:** Los angeles class ssn (688) First End Diameter: 1.1250 inches First End External Thread Length: 2.1400 inches **Second End Diameter:** Between 0.9970 inches and 0.9980 inches **Second End Spline Length:** 1.2900 inches **Second End Spline Minor Diameter:** Between 0.8339 inches and 0.8340 inches **Second End Spline Major Diameter:** 0.9980 inches **Second End Hole Diameter:** 0.4060 inches Step Quantity: **Second End Spline Quantity: Largest Step Diameter:** 1.500 inches **Product Name:** Shaft, hull valve gagging **Special Features:** First end is counteredbored 0.125 inch dia. X 2.560 inch deep. Shaft has 0.125 inch bore drilled 2.530 inchs on side centerline from first end 0.500 inch deep to intersect with end counterbore Material: Steel **Material Specification:** Mil-s-5000 military specification single material response

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 3040-01-486-4251

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200

Mil-std (military Standard):

Mil-s-5000 spec.