

View Online at <https://aerobasegroup.com/nsn/3040-01-494-2724>

**First End Style:**

Circular grooved

**First End Groove Width:**

Between 0.1880 inches and 0.1930 inches

**First End Groove Diameter:**

Between 3.8730 inches and 3.8750 inches

**End Similarity:**

Not identical

**Second End Style:**

Flat keyways and internally threaded

**Overall Length:**

Between 4.020 inches and 4.040 inches

**End Application:**

Gear box, rammer drive

**First End Distance From End To Groove:**

Between 0.107 inches and 0.132 inches

**First End Diameter:**

Between 4.1130 inches and 4.1150 inches

**Second End Keyway Width:**

Between 0.3130 inches and 0.3290 inches

**Second End External Keyway Length:**

Between 1.616 inches and 1.618 inches

**Second End Keyway Depth:**

Between 0.094 inches and 0.110 inches

**Second End Diameter:**

Between 1.9686 inches and 1.9688 inches

**Second End Internal Thread Length:**

1.030 inches

**Step Quantity:**

6

**Largest Step Diameter:**

5.125 inches

**Surface Finish:**

63.0 microinches

**Product Name:**

Cap, adjustment

**Special Features:**

8 internal threads 0.875 x 32 un-3b on second end of shaft; 0.281 diameter through and 0.420 diameter x 0.250 to 0.280 deep counter sunk (6) equally spaced mounting holes on 4.625 pitch circle; next higher assembly nsn 3040-01-492-8053; used on nssn class submarine

**Material:**

Steel

**Material Specification:**

Mil-s-21952, grade hy-80, type b military specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23200

**Mil-std (military Standard):**

Mil-s-21952 spec.