

View Online at <https://aerobasegroup.com/nsn/3040-01-494-2724>

First End Style:

Circular grooved

First End Groove Width:

Between 0.1880 inches and 0.1930 inches

First End Groove Diameter:

Between 3.8730 inches and 3.8750 inches

End Similarity:

Not identical

Second End Style:

Flat keyways and internally threaded

Overall Length:

Between 4.020 inches and 4.040 inches

End Application:

Gear box, rammer drive

First End Distance From End To Groove:

Between 0.107 inches and 0.132 inches

First End Diameter:

Between 4.1130 inches and 4.1150 inches

Second End Keyway Width:

Between 0.3130 inches and 0.3290 inches

Second End External Keyway Length:

Between 1.616 inches and 1.618 inches

Second End Keyway Depth:

Between 0.094 inches and 0.110 inches

Second End Diameter:

Between 1.9686 inches and 1.9688 inches

Second End Internal Thread Length:

1.030 inches

Step Quantity:

6

Largest Step Diameter:

5.125 inches

Surface Finish:

63.0 microinches

Product Name:

Cap, adjustment

Special Features:

8 internal threads 0.875 x 32 un-3b on second end of shaft; 0.281 diameter through and 0.420 diameter x 0.250 to 0.280 deep counter sunk (6) equally spaced mounting holes on 4.625 pitch circle; next higher assembly nsn 3040-01-492-8053; used on nssn class submarine

Material:

Steel

Material Specification:

Mil-s-21952, grade hy-80, type b military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200

Mil-std (military Standard):

Mil-s-21952 spec.