## NSN 3040-01-495-9445

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-495-9445 First End Style: Flat keyway **End Similarity:** Not identical Second End Style: Splined (straight) **Overall Length:** 15.810 inches **End Application:** Cradle handling assembly; seawolf class submarine ssn 23. First End Keyway Width: Between 0.1880 inches and 0.1900 inches First End External Keyway Length: 2.375 inches First End Keyway Depth: Between 0.107 inches and 0.123 inches First End Diameter: Between 0.6230 inches and 0.6240 inches **Second End Diameter:** Between 0.6230 inches and 0.6240 inches **Second End Spline Length:** 1.600 inches **Second End Spline Minor Diameter:** Between 0.5220 inches and 0.5320 inches **Second End Spline Major Diameter:** Between 0.6220 inches and 0.6230 inches Step Quantity: **Second End Spline Quantity:** 10 **Largest Step Diameter:** 1.250 inches **Special Features:** Threaded area 6.0 in length .875-6-acme-2g left hand. Material: Stainless steel **Material Specification:** Astm-a564, ty-630 national specification all material responses Shelf Life: N/a

**Unit Of Measure:** 

## NSN 3040-01-495-9445

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200