NSN 3040-01-496-5682

Shouldered Shaft - Page 1 of 2

First End Style:



View Online at https://aerobasegroup.com/nsn/3040-01-496-5682

Splined (involute) **End Similarity:** Not identical Second End Style: Circular grooved and splined (straight) **Second End Groove Width:** 0.6560 inches **Second End Groove Diameter:** 1.8750 inches **Overall Length:** 10.275 inches **End Application:** Cargo bay rammer chain sprocket box used on seawolf class submarine ssn 23 First End Diameter: Between 2.2920 inches and 2.3120 inches First End Spline Length: 1.375 inches First End Spline Minor Diameter: 2.1078 inches First End Spline Major Diameter: Between 2.2920 inches and 2.3120 inches First End Pressure Angle: 30.0 degrees First End Pitch Diameter: 2.2500 inches **Second End Distance From End To Groove:** 1.714 inches **Second End Diameter:** 2.0930 inches **Second End Spline Length:** 1.714 inches **Second End Spline Minor Diameter:** 1.9210 inches **Second End Spline Major Diameter:** Between 2.1050 inches and 2.1250 inches Step Quantity: First End Spline Quantity: **Second End Spline Quantity:**

NSN 3040-01-496-5682

Shouldered Shaft - Page 2 of 2



Largest Step Diameter:
2.500 inches
Surface Finish:
16.0 microns
Product Name:
Shaft, splined
Special Features:
SECO-ND-SHA-FTEN
Material:
Steel comp 4340
Material Specification:
Dod-f-24669/1 grade 4340 military specification single material response
Specification Data:
81349-dod-f-24669/1 grade 4340 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A23200
Mil-std (military Standard):
spec.