## NSN 3040-01-498-1260 Shouldered Shaft - Page 1 of 2



Shouldered Shart - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/3040-01-498-1260	
First End Style:	
Indented flat keyway	
End Similarity:	
Not identical	
Second End Style:	
Two flat keyways	
Overall Length:	
7.440 inches	
End Application:	
Weapons cradle lashing band release mechanism assembly; la class 688 submarine.	
First End Keyway Width:	
Between 0.5030 inches and 0.5100 inches	
First End External Keyway Length:	
1.0400 inches	
First End Keyway Depth:	
0.1400 inches	
First End Distance From Keyway Center To End:	
0.8950 inches	
First End Diameter:	
Between 1.5500 inches and 1.5650 inches	
Second End Keyway Width:	
Between 0.2500 inches and 0.2520 inches	
Second End External Keyway Length:	
Between 1.1900 inches and 1.2200 inches	
Second End Keyway Depth:	
0.1400 inches	
Second End Diameter:	
Between 0.9982 inches and 0.9990 inches	
Second End Angle Between Keyways:	
180.0 degrees	
Step Quantity:	
2	
Largest Step Diameter:	
1.565 inches	
Special Features:	
Shaft has a total of 5 keyways	

Material:

Stainless steel

**Material Specification:** 

Astm-a564, comp 630 national specification all material responses

Shelf Life:

N/a

## NSN 3040-01-498-1260

Shouldered Shaft - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A23200