## NSN 3040-01-498-9946

View Online at https://aerobasegroup.com/nsn/3040-01-498-9946

Shouldered Shaft - Page 1 of 2



First End Style: Splined (straight) **End Similarity:** Identical Second End Style: Straight splined and externally threaded **Overall Length:** 33.750 inches **End Application:** Main ballast tank vent valve assembly for los angeles class submarine (688) First End Diameter: Between 2.4930 inches and 2.4940 inches First End Spline Length: 10.120 inches First End Spline Minor Diameter: Between 2.1280 inches and 2.1430 inches First End Spline Major Diameter: Between 2.4930 inches and 2.4940 inches **Second End Diameter:** 1.7500 inches **Second End Spline Length:** 4.130 inches **Second End Spline Minor Diameter:** Between 2.1280 inches and 2.1430 inches **Second End Spline Major Diameter:** Between 2.4930 inches and 2.4940 inches Second End External Thread Length: 2.625 inches Step Quantity: First End Spline Quantity: **Second End Spline Quantity:** 10 **Largest Step Diameter:** Between 2.495 inches and 2.497 inches **Surface Finish:** 

32.0 microinches

**Product Name:** 

Shaft

## **Special Features:**

Next higher assembly: motor assembly wp. 0.125 wide x 1.500 diameter groove is provided between 1.750-5unc-3a threads and straight spline on second end of shaft; sae 10 b splines are on both ends in-line

## NSN 3040-01-498-9946

Shouldered Shaft - Page 2 of 2

A23200



Material:
Nickel alloy k-500
Material Specification:
Qq-n-286 form 2, cond annealed & age hardened finish b federal specification single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: