

View Online at <https://aerobasegroup.com/nsn/3040-01-499-6682>

**First End Style:**

Circular grooved and externally threaded

**First End Groove Width:**

0.1250 inches

**First End Groove Diameter:**

0.5000 inches

**End Similarity:**

Not identical

**Second End Style:**

Circular grooved, cross drilled hole, and externally threaded

**Second End Groove Width:**

0.1250 inches

**Second End Groove Diameter:**

0.6250 inches

**Overall Length:**

5.5625 inches

**End Application:**

Hatch, water tight (w.T.), flush, quick acting (q.A.) 24 inch x 30 inch 5 psi je-1153-8

**First End Distance From End To Groove:**

0.750 inches

**First End Diameter:**

0.6250 inches

**First End External Thread Length:**

0.750 inches

**Second End Distance From End To Groove:**

0.625 inches

**Second End Diameter:**

0.7500 inches

**Second End Hole Diameter:**

0.2500 inches

**Second End Distance From Hole Center To End:**

1.000 inches

**Second End External Thread Length:**

0.625 inches

**Second End Hole Depth:**

0.750 inches

**Step Quantity:**

9

**Largest Step Diameter:**

1.250 inches

**Product Name:**

Dog spindle

**Special Features:**

After circular groove, first end has 0.6215-0.6230 inch across flats x 0.6875 long square shoulder. Shaft second end has axial and internal 0.250 inch diameter x 1.000 deep hole and 0.3125-24unf-3a x 0.625 long threads. Center of shaft has 0.875-7 left hand, double lead acme threads with pitch diameter 0.7906-0.8036. Material has magnetic permeability of less than 2.0

**Material:**

Steel comp 304

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23200