

View Online at <https://aerobasegroup.com/nsn/3040-01-499-6682>

First End Style:

Circular grooved and externally threaded

First End Groove Width:

0.1250 inches

First End Groove Diameter:

0.5000 inches

End Similarity:

Not identical

Second End Style:

Circular grooved, cross drilled hole, and externally threaded

Second End Groove Width:

0.1250 inches

Second End Groove Diameter:

0.6250 inches

Overall Length:

5.5625 inches

End Application:

Hatch, water tight (w.T.), flush, quick acting (q.A.) 24 inch x 30 inch 5 psi je-1153-8

First End Distance From End To Groove:

0.750 inches

First End Diameter:

0.6250 inches

First End External Thread Length:

0.750 inches

Second End Distance From End To Groove:

0.625 inches

Second End Diameter:

0.7500 inches

Second End Hole Diameter:

0.2500 inches

Second End Distance From Hole Center To End:

1.000 inches

Second End External Thread Length:

0.625 inches

Second End Hole Depth:

0.750 inches

Step Quantity:

9

Largest Step Diameter:

1.250 inches

Product Name:

Dog spindle

Special Features:

After circular groove, first end has 0.6215-0.6230 inch across flats x 0.6875 long square shoulder. Shaft second end has axial and internal 0.250 inch diameter x 1.000 deep hole and 0.3125-24unf-3a x 0.625 long threads. Center of shaft has 0.875-7 left hand, double lead acme threads with pitch diameter 0.7906-0.8036. Material has magnetic permeability of less than 2.0

Material:

Steel comp 304

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200