NSN 3040-01-500-4804

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-500-4804 First End Style: Flatted **End Similarity:** Not identical Second End Style: Circular grooved and externally threaded **Second End Groove Width:** 0.1900 inches **Second End Groove Diameter:** 0.2700 inches **Overall Length:** 6.375 inches **End Application:** Cargo bay - center/outboard hoist misc assembly for seawolf class ssn 23 First End Flat Depth: Between 0.1250 inches and 0.1270 inches First End Flat Length: 0.810 inches First End Keyway Depth: 0.810 inches **First End Diameter:** Between 0.6230 inches and 0.6250 inches **Second End Distance From End To Groove:** 0.560 inches **Second End Diameter:** 0.3750 inches **Second End External Thread Length:** 0.560 inches Step Quantity: **Largest Step Diameter:** 1.750 inches **Surface Finish:** 32.0 microinches **Special Features:** Second end provided with 0.375-16unc-2a threads. 0.125-0.127 wide x 0.068-0.085 deep keyway slot on second end Material:

Steel comp 304

Material Specification:

Qq-s-763 class-304, condition-a federal specification single material response

Shelf Life:

N/a

NSN 3040-01-500-4804

Shouldered Shaft - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A23200