NSN 3040-01-500-7923

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-500-7923 First End Style: Splined (straight) **End Similarity:** Not identical Second End Style: Circular grooved and externally threaded **Second End Groove Width:** 0.1200 inches **Second End Groove Diameter:** 0.4500 inches **Overall Length:** 14.030 inches **End Application:** Manual remote operator for ahp-33 used on los angeles class ssn (688) First End Diameter: Between 0.7480 inches and 0.7490 inches First End Spline Length: 1.190 inches First End Spline Minor Diameter: Between 0.6290 inches and 0.6390 inches First End Spline Major Diameter: Between 0.7470 inches and 0.7480 inches **Second End Distance From End To Groove:** 1.290 inches **Second End Diameter:** 0.5620 inches Second End External Thread Length: 1.290 inches Step Quantity: First End Spline Quantity: **Largest Step Diameter:** 1.125 inches **Surface Finish:** 32.0 microinches **Product Name:** Shaft **Special Features:** Second shaft end provided with tapered 0.775 inch square x 0.870 inch long after groove

Material:

Nickel alloy k-500

NSN 3040-01-500-7923

Shouldered Shaft - Page 2 of 2



Material	Specific	ation:

Qq-n-286 form 2 condition anneale (cold drawn) & age hardened federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200