NSN 3040-01-500-7923



View Online at https://aerobasegroup.com/nsn/3040-01-500-7923

Shouldered Shaft - Page 1 of 2 First End Style: Splined (straight) **End Similarity:** Not identical Second End Style: Circular grooved and externally threaded Second End Groove Width: 0.1200 inches Second End Groove Diameter: 0.4500 inches **Overall Length:** 14.030 inches **End Application:** Manual remote operator for ahp-33 used on los angeles class ssn (688) **First End Diameter:** Between 0.7480 inches and 0.7490 inches First End Spline Length: 1.190 inches First End Spline Minor Diameter: Between 0.6290 inches and 0.6390 inches First End Spline Major Diameter: Between 0.7470 inches and 0.7480 inches Second End Distance From End To Groove: 1.290 inches Second End Diameter: 0.5620 inches Second End External Thread Length: 1.290 inches **Step Quantity:** 5 First End Spline Quantity: 10 Largest Step Diameter: 1.125 inches Surface Finish: 32.0 microinches **Product Name:** Shaft **Special Features:** Second shaft end provided with tapered 0.775 inch square x 0.870 inch long after groove Material: Nickel alloy k-500

NSN 3040-01-500-7923

Shouldered Shaft - Page 2 of 2



Material Specification:

Qq-n-286 form 2 condition anneale (cold drawn) & age hardened federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200