## NSN 3040-01-501-0189

Shouldered Shaft - Page 1 of 2

Circular grooved and externally threaded

First End Style:

0.1900 inches

First End Groove Width:



View Online at https://aerobasegroup.com/nsn/3040-01-501-0189

First End Groove Diameter:
0.6050 inches
End Similarity:
Not identical
Second End Style:
Circular grooved flat keyway and externally threaded
Second End Groove Width:
0.1900 inches
Second End Groove Diameter:
0.6050 inches
Overall Length:
14.000 inches
End Application:
Retractable bow plane diving ram cylinder zero lk assembly for nssn class submarine
First End Distance From End To Groove:
1.190 inches
First End Diameter:
0.7500 inches
First End External Thread Length:
1.190 inches
Second End Distance From End To Groove:
1.235 inches
Second End Keyway Width:
Between 0.5010 inches and 0.5020 inches
Second End External Keyway Length:
2.312 inches
Second End Keyway Depth:
Between 0.209 inches and 0.226 inches
Second End Diameter:
0.7500 inches
Second End External Thread Length:
1.235 inches
Step Quantity:
8
Largest Step Diameter:
3.250 inches
Surface Finish:
32.0 microinches

## NSN 3040-01-501-0189

Shouldered Shaft - Page 2 of 2



Special	Features:
---------	-----------

Provided with 10b sae splines x 4.440 inch long at 3.955 inch from first end

Material:

Stainless steel

**Material Specification:** 

Astm-a564, type: 630, condition: h1025, hf assn standard single material response

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A23200