NSN 3040-01-501-5680

Straight Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-501-5680

First End Style: Unthreaded cross drilled **End Similarity:** Not identical Second End Style: Flat keyways and internally threaded **Overall Length:** 7.630 inches **End Application:** Center/outboard tray lock/position pin assembly for seawolf class submarine ssn 23 First End Diameter: Between 2.9980 inches and 3.0000 inches First End Hole Diameter: 0.1200 inches First End Distance From Hole Center To End: 1.380 inches First End Hole Depth: Between 0.964 inches and 0.975 inches Second End Keyway Width: Between 0.5060 inches and 0.5080 inches Second End External Keyway Length: Between 3.262 inches and 3.264 inches Second End Keyway Depth: Between 0.1790 inches and 0.1870 inches **Second End Diameter:** Between 2.9980 inches and 3.0000 inches Second End Internal Thread Length: 3.450 inches **Surface Finish:** 32.0 microinches **Product Name:** Pin, lock **Special Features:** Provided with internal 1.000-5 rh acme 2g threads Material: Stainless steel **Material Specification:** Astm-a564, type 630, condition h1150 assn standard single material response Shelf Life: N/a **Unit Of Measure:**

--

NSN 3040-01-501-5680

Straight Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200