NSN 3040-01-501-7753

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-501-7753 **Body Material:** Aluminum alloy **Mounting Provision:** Link **Overall Height:** 3.000 inches **Overall Width:** 20.580 inches **End Application:** Rib high op. Hydraulic outboard motor seastar steering First End Hole Diameter: 0.500 inches **Extended Length:** 28.420 inches **Pressure Rating:** 950.0 pounds per square inch **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Tongue type **Piston Rod End Similarity:** Not identical **Second Piston Rod End Style:** Internal threaded **Second Piston Rod End Thread Series Designator:** Unf **Second Piston Rod End Thread Diameter:** 0.250 inches Second Piston Rod End Thready Qty Per Inch (tpi): **Second Piston Rod End Thread Direction:** Right-hand First End Fork Width: 0.875 inches **Mounting Type And Location:** Screw center section **Port Location And Quantity:** 2 piston rod end

Port Style:

Gasket seal

NSN 3040-01-501-7753

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Inread Series Designator:
Nptf
Port Thread Diameter:
0.250 inches
Port Thready Qty Per Inch (tpi):
28
Special Features:
Piston rod is one piece. Mounted with bracket
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200