NSN 3040-01-502-3016 Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-01-502-3016 First End Style: Square (round corners) **End Similarity:** Not identical Second End Style: Flat keyway and cross drilled hole **Overall Length:** 5.825 inches First End Width Across Flats: Between 0.6240 inches and 0.6260 inches **End Application:** 90 degree angle gearbox assembly; seawolf class sub First End Diameter: Between 0.8030 inches and 0.8130 inches **Second End Keyway Width:** Between 0.1890 inches and 0.1910 inches Second End External Keyway Length: 0.7000 inches Second End Keyway Depth: Between 0.1030 inches and 0.1060 inches **Second End Diameter:** Between 0.6210 inches and 0.6230 inches **Second End Hole Diameter:** Between 0.1350 inches and 0.1420 inches

**Second End Distance From Hole Center To End:** 

0.6250 inches

Second End Hole Depth:

0.6230 inches

Step Quantity:

**Largest Step Diameter:** 

0.813 inches

First End Step Length:

2.8800 inches

**Product Name:** 

Spindle

**Special Features:** 

Modified spindle

Material:

Steel

**Material Specification:** 

Aisi11l41 stl national specification single material response

## NSN 3040-01-502-3016

Shouldered Shaft - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200