## NSN 3040-01-502-4328

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-502-4328 First End Style: Flat keyway **End Similarity:** Not identical Second End Style: Circular grooved and externally threaded **Second End Groove Width:** 0.1200 inches **Second End Groove Diameter:** 1.5430 inches **Overall Length:** 40.690 inches **End Application:** MOTO-R,-ALT-ERNA First End Keyway Width: 0.3770 inches First End External Keyway Length: 2.500 inches First End Keyway Depth: 0.219 inches First End Diameter: 1.6250 inches **Second End Distance From End To Groove:** 0.440 inches **Second End Diameter:** 1.5630 inches **Second End External Thread Length:** 0.440 inches Step Quantity: 21 **Largest Step Diameter:** 4.000 inches **Surface Finish:** 63.0 microinches **Product Name:** Shaft iaw a-445-228 **Special Features:** First end also is internally threaded: 0.500-13 unf-2b; second end threads are: 1.563-18 unc-2a; used on the 150.0 hp alternating current motor p/n a-445-228 Material: Steel comp 316

N/a

Shelf Life:

## NSN 3040-01-502-4328

Shouldered Shaft - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A23200