NSN 3040-01-503-4878



Linear Actuating Cylinder Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-01-503-4878 **Body Material:** Steel, stainless First End Outside Diameter: 0.312 inches **Mounting Provision:** Threaded mounting studs **Tempurature Rating:** 200.0 degrees fahrenheit **Mounting Facility Length:** 1.000 inches **Overall Height:** 8.680 inches **Bore Diameter:** 1.062 inches

Body Outside Diameter:

1.120 inches

Overall Diameter:

1.120 inches

Mounting Facility Thread Class:

2a

Mounting Facility Thread Direction:

Right-hand

First End External Thread Length:

0.500 inches

Compressed Length:

8.680 inches

Extended Length:

12.680 inches

Mounting Provision Arrangement Style:

Single stud

Pressure Rating:

250.0 pounds per square inch

Mounting Facility Thread Series Designator:

Unf

Mounting Facility Thread Diameter:

0.625 inches

Mounting Facility Thready Qty Per Inch (tpi):

18

Integral Valve Operation Method:

Mechanical

Design Characteristics:

Single acting single cylinder

NSN 3040-01-503-4878 Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
0.312 inches
First Piston Rod End Thready Qty Per Inch (tpi):
24
First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Stud piston rod end
Mounting Facility Thread Length:
0.500 inches
Product Name:
Air cylinder
Special Features:
Provide with spring return. Spring force: relaxed 3 pound and compressed 6 pound. Piston rod is high strength carbon steel
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A34200