NSN 3040-01-503-7835



Shouldered Shaft - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/3040-01-503-7835
First End Style:
Square (round corners)
End Similarity:
Not identical
Second End Style:
Circular grooved and flat keyway
Second End Groove Width:
Between 0.0390 inches and 0.0420 inches
Second End Groove Diameter:
0.6030 inches
Overall Length:
4.594 inches
First End Width Across Flats:
Between 0.6240 inches and 0.6260 inches
End Application:
Los angeles class 688; swivel gear joint p/n 12111m502a
First End Diameter:
Between 0.8030 inches and 0.8130 inches
Second End Distance From End To Groove:
Between 0.1370 inches and 0.1400 inches
Second End Keyway Width:
Between 0.1890 inches and 0.1910 inches
Second End External Keyway Length:
0.7500 inches
Second End Keyway Depth:
Between 0.1030 inches and 0.1060 inches
Second End Diameter:
Between 0.6210 inches and 0.6230 inches
Step Quantity:
6
Largest Step Diameter:
Between 0.803 inches and 0.813 inches

First End Step Length:

1.3100 inches

Product Name:

Mod spindle

Special Features:

1 piece mod assembly

Material:

Steel

Shelf Life:

N/a

NSN 3040-01-503-7835

Shouldered Shaft - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A23200