NSN 3040-01-503-7835

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-503-7835

First End Style:

Square (round corners)

End Similarity:

Not identical

Second End Style:

Circular grooved and flat keyway

Second End Groove Width:

Between 0.0390 inches and 0.0420 inches

Second End Groove Diameter:

0.6030 inches

Overall Length:

4.594 inches

First End Width Across Flats:

Between 0.6240 inches and 0.6260 inches

End Application:

Los angeles class 688; swivel gear joint p/n 12111m502a

First End Diameter:

Between 0.8030 inches and 0.8130 inches

Second End Distance From End To Groove:

Between 0.1370 inches and 0.1400 inches

Second End Keyway Width:

Between 0.1890 inches and 0.1910 inches

Second End External Keyway Length:

0.7500 inches

Second End Keyway Depth:

Between 0.1030 inches and 0.1060 inches

Second End Diameter:

Between 0.6210 inches and 0.6230 inches

Step Quantity:

6

Largest Step Diameter:

Between 0.803 inches and 0.813 inches

First End Step Length:

1.3100 inches

Product Name:

Mod spindle

Special Features:

1 piece mod assembly

Material:

Steel

Shelf Life:

N/a

NSN 3040-01-503-7835

Shouldered Shaft - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200

