NSN 3040-01-509-6112

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-509-6112

First End Style:

Circular grooved, cross drilled hole, and externally threaded

First End Groove Width:

0.1200 inches

First End Groove Diameter:

Between 1.0000 inches and 1.0150 inches

End Similarity:

Not identical

Second End Style:

Flatted and internally threaded

Overall Length:

5.610 inches

First End Distance From End To Groove:

2.210 inches

First End Diameter:

Between 1.3720 inches and 1.3730 inches

First End Hole Diameter:

Between 0.1400 inches and 0.1500 inches

First End Distance From Hole Center To End:

0.350 inches

First End External Thread Length:

2.210 inches

Second End Flat Depth:

Between 0.3780 inches and 0.4190 inches

Second End Flat Length:

0.620 inches

Second End Diameter:

Between 1.4980 inches and 1.4990 inches

Second End Internal Thread Length:

2.850 inches

Step Quantity:

2

Largest Step Diameter:

Between 1.498 inches and 1.499 inches

Surface Finish:

63.0 microinches

Special Features:

First end threads are 1.125-12 unf, class 2a; shaft has two grooves - second groove is 1.130 inches from first end groove; second groove diameter is 1.302 to 1.312 inches; two unthreaded cross drilled holes located from step at second end 0.620 inch toward first end along length; cross drilled holes are 0.182 to 0.192 inch diameter positioned 87.0 to 93.0 degrees apart around circumference; internal threads second end are 0.127-27 npt. And intersect cross drilled holes; second end is flatted two sides 1.080 to 1.120 inches across flats

Shelf Life:

N/a

Unit Of Measure:

NSN 3040-01-509-6112

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200