

View Online at <https://aerobasegroup.com/nsn/3040-01-521-3107>

**First End Style:**

Cross drilled and circular grooved

**First End Groove Width:**

1.6720 inches

**First End Groove Diameter:**

0.2500 inches

**End Similarity:**

Not identical

**Second End Style:**

Cross drilled and externally threaded

**Overall Length:**

3.349 inches

**End Application:**

C5 acft

**First End Distance From End To Groove:**

Between 0.070 inches and 0.080 inches

**First End Diameter:**

Between 0.8300 inches and 0.8400 inches

**First End Hole Diameter:**

0.0780 inches

**First End Distance From Hole Center To End:**

0.403 inches

**Second End Diameter:**

0.2500 inches

**Second End Hole Diameter:**

0.0780 inches

**Second End Distance From Hole Center To End:**

0.125 inches

**Second End External Thread Length:**

0.440 inches

**Step Quantity:**

5

**Largest Step Diameter:**

Between 0.299 inches and 0.300 inches

**Product Name:**

Pin, cylinder bearing

**Special Features:**

1first end has 0.109 diameter hole 0.45 inches deep; shaft has .095 diameter crossdrilled hole thru; 1.651 inches center of shaft's crossdrilled hole to first end; t.O. 9h7-3-14-3 fig 5-4 ind 35 and 52; used on hydraulic power transfer package assembly

**Material:**

Steel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A23200