## NSN 3040-01-629-7380

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-629-7380

First End Outside Diameter:
4.5 inches all working ends
Second End Outside Diameter:
4.5 inches all working ends
Mounting Provision:
Unthreaded mounting holes
Overall Width:
6.5 inches
Bore Diameter:
3.0 inches
Overall Diameter:
7.13 inches
End Application:
3805-01-533-1853, loader, scoop type
First End Hole Diameter:
2.005 inches all working ends
Second End Hole Diameter:
2.005 inches all working ends
First End Thickness At Mounting Holes:
6.0 inches all working ends
Second End Thickness At Mounting Holes:
6.0 inches all working ends
Compressed Length:
53.5 inches
Extended Length:
89.0 inches
Pressure Rating:
3000.0 pounds per square inch
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
Bearing type all working ends
Piston Rod End Similarity:
Identical
Second Piston Rod End Style:
Bearing type
First End Largest Inside Diameter:
2.005 inches all working ends
Mounting Type And Location:
Bearing both ends

## NSN 3040-01-629-7380

Linear Actuating Cylinder Assembly - Page 2 of 2



Product Name	P	rod	uct	Na	me	:
--------------	---	-----	-----	----	----	---

Cyl, dipper 5.5bx3.0rx36.0s

**Special Features:** 

Cylinder oins dia: 2.000-2.002 inches, color: black, operating temperature: -25 to 220 degrees f.

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A34200