

View Online at <https://aerobasegroup.com/nsn/3040-01-633-6689>

**First End Style:**

Unthreaded cross drilled

**End Similarity:**

Not identical

**Second End Style:**

Woodruff keyway and internally threaded

**Overall Length:**

Between 7.100 inches and 7.110 inches

**End Application:**

2350-01-577-0830

**First End Diameter:**

Between 0.624 inches and 0.625 inches

**First End Hole Diameter:**

Between 0.125 inches and 0.129 inches

**First End Distance From Hole Center To End:**

1.361 inches

**Second End Keyway Width:**

Between 0.188 inches and 0.190 inches

**Second End External Keyway Length:**

Between 0.198 inches and 0.218 inches

**Second End Internal Thread Length:**

0.515 inches

**Step Quantity:**

1

**Largest Step Diameter:**

Between 0.624 inches and 0.625 inches

**Product Name:**

Shaft, cam, cab lock

**Special Features:**

Thread size for 2nd end internal thread is 0.500-13 unc-2a

**Material:**

Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140

**Material Specification:**

Astm a108 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23200