

View Online at <https://aerobasegroup.com/nsn/3110-00-001-4707>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded

Overall Length:

Between 2.5050 inches and 2.5250 inches

Bore Diameter:

Between 0.1897 inches and 0.1900 inches

Overall Outside Diameter:

Between 0.9590 inches and 0.9790 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.2820 inches and 1.3440 inches

Outer Ring Width:

Between 0.3920 inches and 0.4070 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 2.0210 inches and 2.0410 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Heat stabilized for operation at 250 degrees fah

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp e52100 inner ring

Material Specification:

Mil-s-7420 military specification single material response inner ring

Surface Treatment:

Cadmium shaft

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response shaft

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.