

View Online at <https://aerobasegroup.com/nsn/3110-00-007-0118>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.5000 inches

Overall Length:

Between 1.6260 inches and 1.6980 inches

Overall Outside Diameter:

Between 1.1245 inches and 1.1280 inches

Lubrication Material:

Grease

Stud Diameter:

0.4375 inches

Outer Ring Width:

Between 0.6200 inches and 0.6250 inches

Stud Length:

Between 0.9840 inches and 1.0310 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

Special Features:

Eccentric bushing 0.6240in. Diameter min 0.6260 in. Diameter maximum by 0.5000 in.Lg located 0.5000 in.From end of stud 0.0300 in.Min 0.0330 in. Maximum above center

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100 stud or steel comp e50100 stud

Material Specification:

Mil-m-20693 military specification single material response seal

Surface Treatment:

Cadmium exposed surfaces as mounted or cadmium exposed surfaces as mounted and chromate exposed surfaces as mounted

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification 1st treatment response exposed surfaces as mounted or qq-p-416, type 1, cl 3 federal specification 2nd treatment response exposed surfaces as mounted

Style Designator:

Cam follower

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.