

View Online at <https://aerobasegroup.com/nsn/3110-00-007-0118>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.5000 inches

**Overall Length:**

Between 1.6260 inches and 1.6980 inches

**Overall Outside Diameter:**

Between 1.1245 inches and 1.1280 inches

**Lubrication Material:**

Grease

**Stud Diameter:**

0.4375 inches

**Outer Ring Width:**

Between 0.6200 inches and 0.6250 inches

**Stud Length:**

Between 0.9840 inches and 1.0310 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.438 inches

**Special Features:**

Eccentric bushing 0.6240in. Diameter min 0.6260 in. Diameter maximum by 0.5000 in.Lg located 0.5000 in.From end of stud 0.0300 in.Min 0.0330 in. Maximum above center

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel comp e52100 stud or steel comp e50100 stud

**Material Specification:**

Mil-m-20693 military specification single material response seal

**Surface Treatment:**

Cadmium exposed surfaces as mounted or cadmium exposed surfaces as mounted and chromate exposed surfaces as mounted

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification 1st treatment response exposed surfaces as mounted or qq-p-416, type 1, cl 3 federal specification 2nd treatment response exposed surfaces as mounted

**Style Designator:**

Cam follower

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.