

View Online at <https://aerobasegroup.com/nsn/3110-00-019-8891>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

Between 0.3678 inches and 0.3750 inches

Shank Style:

Externally threaded

Overall Length:

2.5200 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

1.0400 inches

Lubrication Material:

Grease

Shank Thread Length:

1.0000 inches

Outer Ring Width:

Between 0.2090 inches and 0.2190 inches

Inner Ring Width:

0.2810 inches

Length From Bore Center To Shank End:

2.0000 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel shield

Material Specification:

Mil-s-6758 military specification single material response rod end body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Single row, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.