

View Online at <https://aerobasegroup.com/nsn/3110-00-046-3472>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Diameter:

0.6250 inches

Shank Style:

Internally threaded

Overall Length:

3.1590 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

1.5740 inches

Lubrication Material:

Grease

Shank Thread Length:

1.0000 inches

Outer Ring Width:

Between 0.3440 inches and 0.3540 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

2.3750 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

20

Thread Size:

0.437 inches

Self-alignment Angle:

10.00 degrees

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel shield

Material Specification:

Qq-a-225/9 federal specification single material response rod end body

Surface Treatment:

Cadmium shield

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response shield

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.