

View Online at <https://aerobasegroup.com/nsn/3110-00-060-9256>

**Thread Class:**

3b

**Thread Direction:**

Left-hand

**Shank Diameter:**

0.4400 inches

**Shank Style:**

Internally threaded

**Overall Length:**

2.4400 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Overall Outside Diameter:**

1.0000 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 1.0000 inches and 1.0600 inches

**Outer Ring Width:**

Between 0.2090 inches and 0.2190 inches

**Inner Ring Width:**

Between 0.2760 inches and 0.2810 inches

**Length From Bore Center To Shank End:**

1.9400 inches

**Shield Quantity:**

2

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Special Features:**

Hexagonal wrenching flats on end of shank 0.500 in. Across flats

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Stainless steel shield

**Material Specification:**

Mil-s-6758, sae 4130 military specification single material response rod end body

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response

**Style Designator:**

Single row, ball

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.