

View Online at <https://aerobasegroup.com/nsn/3110-00-061-7916>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Diameter:

0.4380 inches

Shank Style:

Internally threaded w/bead

Overall Length:

1.7660 inches

Bore Diameter:

0.1900 inches

Overall Outside Diameter:

0.7810 inches

Lubrication Material:

Grease

Shank Thread Length:

0.7500 inches

Outer Ring Width:

0.3280 inches

Inner Ring Width:

0.4370 inches

Length From Bore Center To Shank End:

1.3750 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Width Across Flats:

0.4380 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Self-alignment Angle:

10.00 degrees

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel rod end body

Material Specification:

66 federal standard single material response outer ring

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.