Rod End Ball Bearing - Page 1 of 2



-00-061-7916

| 0 0 |
|---|
| View Online at https://aerobasegroup.com/nsn/3110-00-06 |
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Shank Diameter: |
| 0.4380 inches |
| Shank Style: |
| Internally threaded w/bead |
| Overall Length: |
| 1.7660 inches |
| Bore Diameter: |
| 0.1900 inches |
| Overall Outside Diameter: |
| 0.7810 inches |
| Lubrication Material: |
| Grease |
| Shank Thread Length: |
| 0.7500 inches |
| Outer Ring Width: |
| 0.3280 inches |
| Inner Ring Width: |
| 0.4370 inches |
| Length From Bore Center To Shank End: |
| 1.3750 inches |
| Shield Quantity: |
| 2 |
| Alignment Type: |
| Self-aligning |
| Self-alignment Location: |
| |
| Width Across Flats: |
| 0.4380 inches |
| Thready Qty Per Inch (tpi): |
| 24 Thread Size: |
| 0.312 inches |
| Self-alignment Angle: |
| |
| 10.00 degrees Lubrication Material Specification: |
| Mil-g-23827 military specification single material response |
| Material: |
| Steel rod end body |
| |
| |

NSN 3110-00-061-7916

Rod End Ball Bearing - Page 2 of 2



Material Specification:

66 federal standard single material response outer ring

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.