

View Online at <https://aerobasegroup.com/nsn/3110-00-079-9960>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.4375 inches

Shank Style:

Externally threaded

Overall Length:

3.0630 inches

Bore Diameter:

Between 0.3122 inches and 0.3125 inches

Overall Outside Diameter:

Between 1.2400 inches and 1.2510 inches

Lubrication Material:

Grease

Shank Thread Length:

1.5630 inches

Outer Ring Width:

0.6500 inches

Inner Ring Width:

0.8700 inches

Length From Bore Center To Shank End:

2.4380 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

Self-alignment Angle:

10.00 degrees

Special Features:

0.0004 in. Maximum radial clearance

Lubrication Material Specification:

Mil-prf-81322 military specification single material response

Material:

Steel shaft

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-prf-81322 spec.