

View Online at <https://aerobasegroup.com/nsn/3110-00-083-1628>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

Hollow

Overall Length:

2.0930 inches

Bore Diameter:

Between 0.2497 inches and 0.2500 inches

Overall Outside Diameter:

0.9380 inches

Lubrication Material:

Grease

Outer Ring Width:

0.4380 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

1.6250 inches

Shank Bore Diameter:

0.5150 inches

Shank Bore Depth:

0.8750 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

External

Self-alignment Angle:

10.00 degrees

Special Features:

Seals bonded to cres inserts

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp e52100 outer ring

Material Specification:

Mil-s-7420 military specification single material response inner ring

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Double row, staggered, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.