

View Online at <https://aerobasegroup.com/nsn/3110-00-121-2370>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Diameter:**

0.4380 inches

**Shank Style:**

Internally threaded w/hexagon end

**Overall Length:**

1.7660 inches

**Bore Diameter:**

0.1900 inches

**Overall Outside Diameter:**

0.7810 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

0.7500 inches

**Outer Ring Width:**

0.3280 inches

**Inner Ring Width:**

0.4375 inches

**Length From Bore Center To Shank End:**

1.3750 inches

**Shield Quantity:**

2

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Width Across Flats:**

0.4375 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

Nas513 keyway across hex head

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel shaft

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Style Designator:**

Double row, staggered, ball

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.