

View Online at <https://aerobasegroup.com/nsn/3110-00-133-6489>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

Between 0.3678 inches and 0.3750 inches

Shank Style:

Externally threaded

Overall Length:

Between 2.3340 inches and 2.3540 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 1.0520 inches and 1.0720 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.0940 inches and 1.1560 inches

Outer Ring Width:

Between 0.3490 inches and 0.3690 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 1.8030 inches and 1.8230 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Lubricated 40 to 50 percent full

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp e52100 roller

Material Specification:

Ams 3652 assn standard single material response seal

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.