NSN 3110-00-138-0072

Needle Bearing Cam Follower - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-138-0072 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.3160 inches **Overall Length:** 1.6780 inches **Overall Outside Diameter:** 0.7500 inches **Lubrication Material:** Grease Stud Diameter: 0.2500 inches **Outer Ring Width:** 0.2810 inches Stud Length: 1.3660 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Special Features:** Nas516-1 lubrication fitting in stud end; 100 pct magnetic particle inspected/magnafluxed; outer ring to be heat treated to rockwell c58-63; od crowned on a 10 in. Radius; specified lubricant plus 10 pctmos2 **Lubrication Material Specification:** Mil-g-81322 military specification single material response Material: Steel stud **Material Specification:** Maraging-vascomax 350 cvm mfr ref single material response outer ring **Surface Treatment:** Cadmium all external/exposed metal surfaces **Style Designator:** Cam follower **Thread Series Designator:** Unf **Specification Data:** 81755-c4293 manufacturers specification

N/a

Shelf Life:

Unit Of Measure:

NSN 3110-00-138-0072

Needle Bearing Cam Follower - Page 2 of 2



| _ | | | | | | | | | | |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | 2 | iza | 31 | ^ | n | |
| | | | | | | | | | | |

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.