

View Online at <https://aerobasegroup.com/nsn/3110-00-175-7910>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.3750 inches

**Overall Length:**

Between 1.2620 inches and 1.3390 inches

**Overall Outside Diameter:**

Between 0.6245 inches and 0.6260 inches

**Lubrication Material:**

Grease

**Stud Diameter:**

Between 0.3115 inches and 0.3125 inches

**Outer Ring Width:**

Between 0.4630 inches and 0.4930 inches

**Stud Length:**

Between 0.7990 inches and 0.8460 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Special Features:**

Nas516-1 lubrication fitting in screwdriver slot, outer ring heat treated to rockwell c58-63

**Lubrication Material Specification:**

Mil-g-81322 military specification single material response

**Material:**

Steel stud

**Material Specification:**

Vascomax 350 cvm, 81755 mfr ref single material response outer ring

**Surface Treatment:**

Cadmium outer ring

**Style Designator:**

Cam follower

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-g-81322 spec.