Needle Bearing Cam Follower - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-175-7966

View Online at https://aerobasegroup.com/nsn/3110-00-175-7966
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.3750 inches
Overall Length:
Between 1.2620 inches and 1.3390 inches
Overall Outside Diameter:
Between 0.6245 inches and 0.6260 inches
Lubrication Material:
Grease
Stud Diameter:
Between 0.3115 inches and 0.3125 inches
Outer Ring Width:
Between 0.4630 inches and 0.4930 inches
Stud Length:
Between 0.7990 inches and 0.8460 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.312 inches
Special Features:
Nas516-1 lubrication fitting in sd end and outer ring heat treated to rockwell c58-63
Lubrication Material Specification:
Mil-g-81322 military specification single material response
Material:
Steel stud
Material Specification:
Vascomax 350 cvm, 81755 mfr ref single material response outer ring
Surface Treatment:
Cadmium outer ring
Style Designator:
Cam follower
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Needle Bearing Cam Follower - Page 2 of 2



Fiig: A044a0

Mil-std (military Standard):

Mil-g-81322 spec.