

View Online at <https://aerobasegroup.com/nsn/3110-00-183-9894>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded

Overall Length:

2.3360 inches

Bore Diameter:

0.2500 inches

Overall Outside Diameter:

1.0468 inches

Lubrication Material:

Grease

Shank Thread Length:

1.0000 inches

Outer Ring Width:

0.3594 inches

Inner Ring Width:

0.5000 inches

Length From Bore Center To Shank End:

1.8125 inches

Shield Quantity:

2

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Grease plug on lower half of bearing, radial play 0.0001 to 0.0005 in.

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel shield and stainless steel shield

Surface Treatment:

Cadmium shield

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.