NSN 3110-00-198-1010

Bell Crank Ball Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-198-1010
Bore Diameter:
Between 0.2495 inches and 0.2500 inches
Lubrication Material:
Grease
Flange Outside Diameter:
Between 1.6150 inches and 1.6350 inches
Flange Width:
Between 0.0570 inches and 0.0670 inches
Outer Ring Width:
Between 0.4950 inches and 0.5050 inches
Inner Ring Width:
Between 0.6200 inches and 0.6250 inches
Outer Ring Outside Diameter:
Between 0.7400 inches and 0.7600 inches
Rivet Hole Diameter:
Between 0.1400 inches and 0.1450 inches
Retainer Fabrication Method:
Machined
Seal Quantity:
2
Bearing Seal Type:
Contact
Rivet Hole Quantity:
12
Distance Between Flange Hole Centers:
Between 1.3070 inches and 1.3170 inches
Lubrication Material Specification:
Mil-g-23827 military specification single material response
Material:
Steel comp e52100 retainer
Material Specification:
Aisi assn standard single material response retainer
Surface Treatment:
Cadmium bore
Surface Treatment Specification:
Qq-p-416, type 1, class 2 federal specification single treatment response bore
Style Designator:
Double row ball, double closure, rigid inner ring extended both sides
Shelf Life:
N/a
Unit Of Measure:

NSN 3110-00-198-1010

Bell Crank Ball Bearing - Page 2 of 2



Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.