NSN 3110-00-198-1010

Bell Crank Ball Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-198-1010

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Lubrication Material:

Grease

Flange Outside Diameter:

Between 1.6150 inches and 1.6350 inches

Flange Width:

Between 0.0570 inches and 0.0670 inches

Outer Ring Width:

Between 0.4950 inches and 0.5050 inches

Inner Ring Width:

Between 0.6200 inches and 0.6250 inches

Outer Ring Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Rivet Hole Diameter:

Between 0.1400 inches and 0.1450 inches

Retainer Fabrication Method:

Machined

Seal Quantity:

2

Bearing Seal Type:

Contact

Rivet Hole Quantity:

12

Distance Between Flange Hole Centers:

Between 1.3070 inches and 1.3170 inches

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100 retainer

Material Specification:

Aisi assn standard single material response retainer

Surface Treatment:

Cadmium bore

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response bore

Style Designator:

Double row ball, double closure, rigid inner ring extended both sides

Shelf Life:

N/a

Unit Of Measure:

NSN 3110-00-198-1010

Bell Crank Ball Bearing - Page 2 of 2

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.

