

View Online at <https://aerobasegroup.com/nsn/3110-00-198-1552>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Diameter:**

0.6870 inches

**Shank Style:**

Internally threaded

**Overall Length:**

3.0460 inches

**Bore Diameter:**

0.3125 inches

**Overall Outside Diameter:**

Between 1.3600 inches and 1.4100 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 1.3100 inches and 1.3700 inches

**Outer Ring Width:**

0.4600 inches

**Inner Ring Width:**

0.6870 inches

**Length From Bore Center To Shank End:**

2.3120 inches

**Seal Quantity:**

2

**Shield Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Width Across Flats:**

0.6870 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.500 inches

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

With means for relubrication, 0.0700 in. Diameter inspection hole

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel snap ring

**Material Specification:**

Qq-s-763 federal specification single material response shield

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

**Style Designator:**

Single row, concave rollers

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.