

View Online at <https://aerobasegroup.com/nsn/3110-00-232-7979>

Overall Width:

Between 0.7200 inches and 0.7500 inches

Bore Diameter:

Between 3.9997 inches and 4.0000 inches

Overall Outside Diameter:

Between 4.6247 inches and 4.6250 inches

Lubrication Material:

Grease

Surface Finish:

Ground

Retainer Fabrication Method:

Machined

Seal Quantity:

2

Bearing Seal Type:

Contact

Load Direction:

Angular

Internal Fit-up Designation:

Standard

Contact Angle:

30.0 degrees

Special Features:

Etch v on bores and od of bearings at high points of radial runout, 0.0003 radial runout inner ring, 0.0004 radial runout outer ring; kaydon precision coss 4, fscm 32828

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100 outer ring

Material Specification:

Aisi assn standard single material response outer ring

Surface Treatment:

Varnish seal

Surface Treatment Specification:

Mil-v-173 military specification single treatment response seal

Style Designator:

Counterbored outer rings, non-separable, back to back mounting

Test Data Document:

32828-63-44-24-1-2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.