

View Online at <https://aerobasegroup.com/nsn/3110-00-235-2414>

**Shank Diameter:**

Between 0.6230 inches and 0.6250 inches

**Shank Style:**

Hollow

**Overall Length:**

2.7190 inches

**Bore Diameter:**

Between 0.2498 inches and 0.2500 inches

**Overall Outside Diameter:**

0.9380 inches

**Lubrication Material:**

Grease

**Outer Ring Width:**

0.4380 inches

**Inner Ring Width:**

Between 0.5880 inches and 0.5930 inches

**Length From Bore Center To Shank End:**

2.2500 inches

**Shank Bore Diameter:**

Between 0.5000 inches and 0.5150 inches

**Shank Bore Depth:**

0.8750 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

0.0004 in. Maximum radial clearance, starting torque 0.052 inch lbs max, shank void filled with narmco 3119 putty, 0.015 in. By 45 degrees chamfer on od of shank

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel rod end body

**Style Designator:**

Double row, staggered, ball

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.